

# Sigma DS3 Direct-to-Card Printer

#### **HIGHLIGHTS**

### Sigma: The next generation of direct-to-card printing

Entrust Sigma ID Card Printers are specifically designed for today's cloud environments and give you the ability to easily issue secure identities.

- Simple: From unboxing to issuing ID cards and mobile flashpasses to managing your printer, we made sure Sigma was the most user-friendly ID card issuance solution in the world
- **Secure:** Our industry-leading issuance security architecture will keep your cards and your customers' data safe and secure each step of the issuance process
- Smart: Forward-thinking technology and scalability allow you to expand your ID card program as your needs evolve

#### **KEY FEATURES & BENEFITS**

## The world's most user-friendly ID card printer

- Intuitive printer dashboard lets you see printer status, order supplies, check cleaning status, update firmware, or contact help - all from your mobile device
- Seamless self-service lets you access how-to videos and other helpful resources by simply scanning a QR code on the LCD display
- Variable LED light ring lets you incorporate brand colors or other customization into your ambient environment
- Pre-loaded ribbon cassettes make switching ribbons easy



### Sigma DS3 Direct-to-Card Printer

### **Unmatched security**

- Optional locks
- Secure boot protects system from malware or virus on boot-up
- Trusted Platform Module (TPM) manages the printer's own TLS/SSL certificates and keys
- Connection and data sent between software and printer is encrypted
- Customer data is encrypted and is not stored in the printer after printing is complete
- Luster printing and other security features added to cards protect from tampering and counterfeiting

### Flexibility and scalability built for the future

- Issuance capabilities include physical cards and digital mobile flashpass
- Choose on-premises or cloud-hosted deployment
- Expand your ID program as your needs change by adding multi-hopper, smart card capabilities, color tactile printing, and more

STUDENT ID

 Print anytime, anywhere with your mobile device (iOS, Android, Windows)





### Sigma DS3 Direct-to-Card Printer

#### **TECHNICAL SPECIFICATIONS**

#### **Standard Features & Supplies**

| Print technology      | Dye sublimation  |  |
|-----------------------|--|--|
| Print capabilities    | Single- or dual-sided  |  |
| Print resolution      | 300 dots per inch (dpi) (300 X 600, 300 X 1200)  |  |
| Monochrome printing   | Up to 1,100 cards per hour single-sided  |  |
| Print speed           | Single-sided color ribbon: up to 250 cards per hour (cph)<br>Double-sided color ribbon: up to 180 cards per hour (cph) |  |
| Card capacity         | Input hopper: 125 cards<br>Output hopper: 25 cards   |  |
| Card sizes            | Thickness: 0.010 inches to 0.040 inches (0.25mm - 1.016mm)<br>Dimension: ID-1, CR-79, CR-80                            |  |
| Operating environment | Temperature: 60°F to 95°F (15°C to 35°C)<br>Humidity: 20-80% RH – non condensing                                       |  |
| Physical dimensions   | L 17.4 in x W 8.9 in x H 9 in / 44.2 cm x 22.6 cm x 22.9 cm  |  |
| Weight                | 12.1 lbs (5.49 kg); varies with options  |  |
| Connectivity          | USB and Ethernet   |  |
| Warranty              | 36 months  |  |





### Sigma DS3 Direct-to-Card Printer

#### **Optional Features & Supplies**

| Magnetic stripe encoding | ISO 7811 three-track support (high- and low-coercivity) JIS Type II single-track option   |                |  |
|--------------------------|---|----------------|--|
| WiFi                     | WiFi types: 802.11g/n<br>Authentication modes: None, WPA2 Personal<br>Dual-band 2.4GHz & 5GHz   |                |  |
| Smart card encoding      | Single wire or loosely coupled: • Contact smart card encoding: ISO 7816 T=0 (T=1), Class A 5V (3V and 1.8V) • Contactless smart card encoding: ISO 14443 A/B, ISO 15693, MIFARE, MIFARE DESFire EV1/EV2, HID Prox, iClass, iClass SE, iClass Seos, Felica |                |  |
| Color ribbons*           | YMCKT   | 250/500 images |  |
|                          | ymcKT   | 650 images     |  |
|                          | YMCKT-KT  | 350 images     |  |
|                          | KT  | 1,000 images   |  |
|                          | KTT   | 750 images     |  |
|                          | YMCKF-KT  | 300 images     |  |
|                          | YMCKL-KT  | 300 images     |  |
|                          | ST-KT   | 500 images     |  |
|                          | GT-KT   | 500 images     |  |
|                          | YMCK & YMCK-KK  | 500 images     |  |
| Monochrome ribbons       | Black, white, blue, red, green, scratch-off, silver matte, gold matte, silver metallic, and gold metallic: 1,500 images   |                |  |

<sup>\*</sup> Color ribbon guide: Y=Yellow, M=Magenta, C=Cyan, K=Black, T=Topcoat, F=UV fluorescent, L=Luster, y=1/2 panel Yellow, m=1/2 panel Magenta, c=1/2 panel Cyan, S=Silver matte, G=Gold matte.